

## SILSTAR CHAINWHEELS



AX-5RG II



AX-5SDII AH

**Model AX-5RG II**  
**APEX-5RG II**

Crank : Length 165mm(6½") or 170mm(6¾")  
Thread BC $\frac{9}{16}$ " $\times$ 20T or M14 $\times$ P1.25  
Chainring : Size  $\frac{1}{2}$ " $\times$  $\frac{3}{8}$ "(2mm)  
Outer 48 to 54 teeth  
Inner 36, 39, 40 and 42 to 48 teeth (standard teeth 52T $\times$ 40T)

Interchangeable with SAKAE AX-5RG I.  
Weight : Crank set 600g (21 oz)  
Available with light alloy chainguard if requested.  
Model No. CG-111.

**Model AX-5SDII AH**  
**APEX-5SDII AH**

Changeable only inner chainring.  
Crank : Length 165mm(6½") or 170mm(6¾")  
Thread BC $\frac{9}{16}$ " $\times$ 20T or M14 $\times$ P1.25  
Chainring : Size  $\frac{1}{2}$ " $\times$  $\frac{3}{8}$ "(2mm)  
Outer 48 to 54 teeth  
Inner 36, 39, 40, and 42 to 48 teeth (standard teeth 52T $\times$ 40T)

Interchangeable with SAKAE AX-5RG II.  
Weight : Crank set 595g (20.8 oz)  
Available with light alloy chainguard if requested.  
Model No. CG-111.

**APEX BOTTOM BRACKET SET**

Bracket Width	AXLE Number	CUP THREAD			Full length	Chain line
		Left	Center	Right		
68	3P	42.5mm	52mm	45.5mm	140mm	42.0mm
*	3SS	*	*	48.0	142.5	44.5
*	3T	45.5	*	49.5	147.0	46.0
*	3U	*	*	51.0	148.5	47.5
70	5P	41.0	55	44.0	140.0	42.0
*	5SP	*	*	48.0	144.0	46.0
*	5SS	42.5	*	48.0	145.5	46.0
*	5T	45.5	*	49.5	150.0	47.5
*	5U	*	*	51.0	151.5	49.0



Square Slope : 2" Weight : 355g(12.4 oz)



SI-5DRGAH



SI-5DRGE

Melt-forged high-strength light alloy Cotterless cranks. Interchangeable with all SAKAE APEX axle.

**Model SI-5DRG AH**  
**SILSTAR-5DRG AH**

Mounted on Melt-forged five arm. Five-arm bright finished. 14S Super Duralumin chainrings.  
Crank : Length 165mm(6½") 170mm(6¾") 175mm(7")  
Thread BC $\frac{9}{16}$ " $\times$ 20T or M14 $\times$ P1.25  
Chainring : Size  $\frac{1}{2}$ " $\times$  $\frac{3}{8}$ "(2mm)  
Outer 48 to 54 teeth  
Inner 36, 39, 40, 42 and 44 to 48 teeth (standard teeth 52T $\times$ 40T)  
Interchangeable with SAKAE AX-5RG II  
Weight : Crank set 610g(21.3 oz)  
Available with light alloy chainguard if requested.  
Model No. CG-110.

**Model SI-5DRG E**  
**SILSTAR-5DRG E**

Mounted on Melt-forged five arm. Five-arm bright finish, chainrings C-P Steel glossless.  
Crank : Length 165mm(6½") 170mm(6¾") 175mm(7")  
Thread BC $\frac{9}{16}$ " $\times$ 20T or M14 $\times$ P1.25  
Chainring : Size  $\frac{1}{2}$ " $\times$  $\frac{3}{8}$ "(2mm)  
Outer 48 to 54 teeth  
Inner 36, 39, 40, 42 and 44 to 48 teeth (standard teeth 52T $\times$ 40T)  
Interchangeable with SAKAE AX-5RG II  
Weight : Crank set 870g(30.4 oz)  
Available with chainguard if requested.  
Model No. CG-110, CG-550L, S.