

FRAME ORDER SYSTEM

● **ULTIMATE SUPERLIGHT MTB** ● **ULTIMATE ULTRALIGHT MTB** ● **ULTIMATE ULTRASTRONG**

PRESTIGE ULTIMATE SUPERLIGHT MTB Tube

| Product | Description | Part No. | Outside Diameter D | Thickness T ₁ -T ₂ -T' ₁ | Butted Part | | Tapered Part | | Thinned Part C | Total Length L | Weight (g) |
|------------|-------------|----------|--------------------|---|----------------|-----------------|----------------|-----------------|----------------|----------------|------------|
| | | | | | ℓ ₁ | ℓ' ₁ | ℓ ₂ | ℓ' ₂ | | | |
| Top Tube | D.B.T. | 4413 | 28.6 | 0.8-0.5-0.8 | 80 | 190 | 70 | 70 | 240 | 650 | 285 |
| | D.B.T. | 4414 | 30.0 | 0.8-0.5-0.8 | 80 | 190 | 70 | 70 | 240 | 650 | 302 |
| Top & Down | D.B.T. | 4433 | 31.8 | 0.8-0.5-0.8 | 80 | 170 (220) | 70 | 70 | 260 (210) | 650 | 320 |
| Down Tube | D.B.T. | 4434 | 33.0 | 0.8-0.5-0.8 | 80 | 160 | 70 | 70 | 270 | 650 | 319 |
| | D.B.T. | 4443 | 34.9 | 0.8-0.5-0.8 | 80 | 150 | 70 | 70 | 280 | 650 | 345 |
| Seat Tube | New B.B.T. | 4458 | 28.6/29.3 | 0.9-0.6-1.3 | | | | | | | |
| | New B.B.T. | 4456 | 31.8/32.5 | 0.9-0.6-1.3 | | | | | | | |
| Head Tube | P.G. | 3406 | 33.0 | 1.5 | — | — | — | — | — | 200 | |
| | P.G. | 3407 | 36.4 | 1.2 | — | — | — | — | — | 200 | |
| | P.G. | 3408 | 37.0 | 1.5 | — | — | — | — | — | 200 | |

| Product | Description | Part No. | Outside Diameter | | Thickness T | Straight Part ℓ ₁ | Tapered Part ℓ ₂ | Total Length L | Weight (g) |
|------------|-------------|----------|--------------------|----------------|----------------|------------------------------|-----------------------------|----------------|------------|
| | | | D ₁ | D ₂ | | | | | |
| Seat Stay | ST.P. | 4502 | 15.9 | 12.0 | 0.7 | 280 | 320 | 600 | |
| Chain Stay | CW-3 | 4552 | 22.2 | 13.0 | 0.8-0.6-0.8 | 140 | 300 | 440 | |
| | CW-5 | 4556 | 22.2 | 13.0 | 0.8-0.6-0.8 | 140 | 300 | 440 | |
| Fork Blade | S.B.T. | 3613 | 28.6 | 16.5 | 1.2-1.0 | 130 | 300 | 430 | 505 |
| | S.B.T. | 3615 | 28.6 | 20.0 | 1.2-0.9 | 130 | 300 | 430 | 545 |
| | Oval | 3614 | 27.0 (31.0 x 23.0) | | 1.2 Even-thick | 130 | 300 | 430 | 334 |

PRESTIGE ULTIMATE ULTRALIGHT MTB Tube

| Product | Description | Part No. | Outside Diameter D | Thickness T ₁ -T ₂ -T' ₁ | Butted Part | | Tapered Part | | Thinned Part C | Total Length L | Weight (g) |
|------------|----------------|----------|--------------------|---|----------------|-----------------|----------------|-----------------|----------------|----------------|------------|
| | | | | | ℓ ₁ | ℓ' ₁ | ℓ ₂ | ℓ' ₂ | | | |
| Top Tube | D.B.T. | 4412 | 28.6 | 0.9-0.5-0.9 | 80 | 190 | 70 | 70 | 240 | 650 | 317 |
| Top & Down | D.B.T. | 4432 | 31.8 | 0.9-0.5-0.9 | 80 | 170 (220) | 70 | 70 | 260 (210) | 650 | 348 |
| Down Tube | D.B.T. | 4442 | 34.9 | 0.9-0.5-0.9 | 80 | 150 | 70 | 70 | 280 | 650 | 376 |
| Seat Tube | B.B.T. | 3456 | 31.8/33.2 | 0.9-0.6-1.3 | | | | | | | |
| | Tapered S.B.T. | 3454 | 31.8 | 1.0/0.9-0.6 | | | | | | | |
| | B.B.T. | 3458 | 28.6/30.0 | 0.9-0.6-1.3 | | | | | | | |
| | S.B.T. | 3452 | 28.6 | 0.9-0.6 | | | | | | | |
| Head Tube | P.G. | 3406 | 33.0 | 1.5 | — | — | — | — | — | 200 | |
| | P.G. | 3407 | 36.4 | 1.2 | — | — | — | — | — | 200 | |
| | P.G. | 3408 | 37.0 | 1.5 | — | — | — | — | — | 200 | |

| Product | Description | Part No. | Outside Diameter | | Thickness T | Straight Part ℓ ₁ | Tapered Part ℓ ₂ | Total Length L | Weight (g) |
|------------|-------------|----------|------------------|----------------|----------------|------------------------------|-----------------------------|----------------|------------|
| | | | D ₁ | D ₂ | | | | | |
| Seat Stay | ST.P. | 4502 | 15.9 | 12.0 | 0.7 | 280 | 320 | 600 | |
| Chain Stay | CW-3 | 3552 | 22.2 | 13.0 | 0.8 Even-thick | 140 | 300 | 440 | |
| | CW-4 | 3554 | 22.2 | 13.0 | 0.8 Even-thick | 140 | 300 | 440 | |
| | CW-5 | 3556 | 22.2 | 13.0 | 0.8 Even-thick | 140 | 300 | 440 | |

See above about Fork Blade.
See right page about Fork Stem.

PRESTIGE ULTIMATE ULTRASTRONG MTB Tube

| Product | Description | Part No. | Outside Diameter D | Thickness T ₁ -T ₂ -T' ₁ | Butted Part | | Tapered Part | | Thinned Part C | Total Length L | Weight (g) |
|------------|----------------|----------|--------------------|---|----------------|-----------------|----------------|-----------------|----------------|----------------|------------|
| | | | | | ℓ ₁ | ℓ' ₁ | ℓ ₂ | ℓ' ₂ | | | |
| Top Tube | D.B.T. | 4415* | 28.6 | 1.0/0.7-0.7/0.7-1.0/0.7 | 100 | 160 | 50 | 50 | 290 | 650 | 375 |
| Top & Down | D.B.T. | 4435 | 31.8 | 1.0/0.7-0.7/0.7-1.0/0.7 | 100 | 160 | 50 | 50 | 290 | 650 | 419 |
| Down Tube | D.B.T. | 4445 | 34.9 | 1.0/0.7-0.7/0.7-1.0/0.7 | 100 | 160 | 50 | 50 | 290 | 650 | 461 |
| Seat Tube | B.B.T. | 3456 | 31.8/33.2 | 0.9-0.6-1.3 | | | | | | | |
| | Tapered S.B.T. | 3454 | 31.8 | 1.0/0.9-0.6 | | | | | | | |
| | B.B.T. | 3458 | 28.6/30.0 | 0.9-0.6-1.3 | | | | | | | |
| | S.B.T. | 3452 | 28.6 | 0.9-0.6 | | | | | | | |
| Head Tube | P.G. | 3406 | 33.0 | 1.5 | — | — | — | — | — | 200 | |
| | P.G. | 3407 | 36.4 | 1.2 | — | — | — | — | — | 200 | |
| | P.G. | 3408 | 37.0 | 1.5 | — | — | — | — | — | 200 | |

*D.B.T.: Ditched Double Butted Tube.

| Product | Description | Part No. | Outside Diameter | | Thickness T | Straight Part ℓ ₁ | Tapered Part ℓ ₂ | Total Length L | Weight (g) |
|------------|-------------|----------|------------------|----------------|----------------|------------------------------|-----------------------------|----------------|------------|
| | | | D ₁ | D ₂ | | | | | |
| Seat Stay | ST.P. | 4502 | 15.9 | 12.0 | 0.7 | 280 | 320 | 600 | |
| Chain Stay | CW-3 | 3552 | 22.2 | 13.0 | 0.8 Even-thick | 140 | 300 | 440 | |
| | CW-4 | 3554 | 22.2 | 13.0 | 0.8 Even-thick | 140 | 300 | 440 | |
| | CW-5 | 3556 | 22.2 | 13.0 | 0.8 Even-thick | 140 | 300 | 440 | |

See left page about Fork Blade.

PRESTIGE MTB Fork Stem

| Product | Part No. | D ₁ | D ₂ | T ₁ | T ₂ | ℓ | L | Weight (g) |
|---------|----------|----------------|----------------|----------------|----------------|----|-----|------------|
| | | | | | | | | |
| | 3707 | 28.6 | 25.4 | 2.3 | 1.6 | 65 | 280 | 332 |